

Client:	Alstom Power Gen.	ADAMS Order-No.:	13-0611-025 / 05
Project:	Maritza East 1	ADAMS Serial-No.:	81026 + 81028
Order-No.:	D61-4500056424	Production Year:	2007
Ident-No.:	*		
Marking:	--		

Valve Type:	SCV	Nominal Size:	250 / 10"
Operation:	Non Return Valve	Body Connection:	Welding End
Medium:	Saturated Steam	Flange acc. to:	--
Fluid Group:	--	Flange Connection:	--
Design:	AD 2000	Body Rating:	PN 40
		Trim Rating:	PN 40

Operating Data

Operating Temperature:	458 °C		
Operat. Pres.:	22,6 bar at	458 °C	
Δp:	22,6 bar at	458 °C	

Design Data

max. allow. Temp.:	466 °C		
max. allow. Pres.:	27,1 bar at	466 °C	
max. allow. Δp:	22,6 bar at	466 °C	
Δp Actuator:	0 bar		

Gear:	--
Actuator:	RCQ250 SR80
Stroking Time:	1.0 sec.
Voltage:	--

Accessories:	Fisher 67CF Filter Regulator
	P&F Inductive Proximity Switch
	Norgren Quick Venting Valve
	Norgren 3/2 Directional Control Valve

Documentation

Assembly DWG:	0611.025.005.30A.01.2-B
Parts List:	0611.025.005.30B.01.4-A
Dimensional DWG:	0611.025.005.30O.01.4-B
Installation, Operation & Maintenance Manual:	30Z.03.A
QS-Documentation:	QS-0611-025-05
Data Sh./Characteristic:	--
Instrumentation:	--
Calculation:	--

* 81026 = 01LBQ60AA010
81028 = 02LBQ60AA010

Material

Valve Body:	1.7357
Disc:	1.4923
Shaft:	A564TP630H1150-D
Sealing:	--



**The operator has to guarantee, that the valve is only use for the specified medium. Above-mentioned datas of pressure and temperatures must not be exceeded.
The valve and equipment can be a source of serious danger due to improper use.**

Original	Date:	31.7.2007	Prepared by:	Ev / Sw
Rev. 01	Date:		Prepared by:	
Description:				